

☐ In my patents list | Print

AN ADDITIVE TO RENDER GYPSUM BOARD MOISTURE RESISTANT

Bibliographic data Description Claims Mosaics Original document INPADOC legal status

Publication number: EP1556313 (A1)

Publication date: 2005-07-27

Inventor(s): HASSAN AZIZ [US]; BORSINGER GREGORY [US]

Applicant(s): HRD CORP [US]

Classification:






- international: C04B24/08; C04B28/14; C04B24/00; C04B28/00; (IPC1-7): C04B28/14; C04B24/08; E04C2/04

- European: C04B24/08; C04B28/14

Application number: EP20030777575 20031009

Priority number(s): WO2003US32391 20031009; US20020417620P 20021010


Also published as:

 EP1556313 (B1)
 WO2004033388 (A1)
 WO2004033388 (B1)
 DE60310442 (T2)
 CA2501509 (A1)[View INPADOC patent family](#)[View list of citing documents](#)[View document in the European Register](#) [Report a data error here](#)

Abstract not available for EP 1556313 (A1)

Abstract of corresponding document: WO 2004033388 (A1)

Waxes prepared from hydrogenated plant oils, such as palm and soybean, are used to render gypsum board resistant to water. Unlike petroleum-derived waxes used for the same purpose, vegetable derived waxes are renewable and readily converted into forms such as emulsions or powder that facilitate incorporation into gypsum board manufacturing. Such water resistant materials are characterized by enhanced moisture barrier properties. The compositions have a low iodine value (between 2-5), and melting points between approximately 120-185 degrees F (Mettler Drop Point). The wax comprises a triglyceride whose fatty acids are predominantly stearic acid (C18). The composition is used as an additive in the manufacture of water resistant gypsum board.



Data supplied from the esp@cenet database — Worldwide